

MS-H340-S4

LCD 4-Channel Digital Magnetic Hotplate Stirrer



It is widely used in chemical synthesis, physical and chemical analysis, bio pharmaceuticals etc.

Features

- Independent heating and stirring control for each position
- LCD display shows real-time temperature and speed
- PID controller ensures a precise and stable heating process (maximum temperature up to 340°C)
- Brushless DC motor is quiet, reliable & maintenance free, and provides more powerful speed control
- External temperature sensor (PT1000) with accuracy 0.2°C
- Overheating protection temperature at 420°C
- Stainless steel work plate with ceramic coating provides good chemical resistance
- Wide variety of accessories available to choose from



Specifications	MS-H340-S4
Work plate dimension	Ø135mm(5inch) x4
Plate material	Aluminium with ceramic coating
Motor type	Brushless DC motor
Stirring positions	4
Max. stirring quantity of single position (H ₂ O)	10L x 4
Max. magnetic bar	40mm
Speed range	200-1500rpm
Speed display	LCD
Temperature display	LCD
Control accuracy of sensor	±20rpm
Temperature range	25-340°C
Over temperature protection	420°C
Heating liquid control accuracy	±1°C(<100°C), ±1%(>100°C)
Temperature display accuracy	±0.1°C
External temperature sensor	PT1000(accuracy±0.2°C)
IP Protection class	IP20
Motor output power	1.8Wx4
Power	1210W×2
Heating Power	1100W×2
Voltage,Frequency	100-120V,60Hz; 200-240V,50 Hz
Dimensions[WxDxH]	698x270x128mm
Weight	9.5kg
Permissible ambient temperature	5~40°C
Permissible relative humidity	80%RH